

SPECIFICATIONS

B

PHYSICAL

| | |
|------------------------|--|
| Size (L x W x H) | 537 x 269 x 263 mm (21.1 x 10.6 x 10.4 in) |
| Weight..... | 8.8 kg (19.4 lbs) |

SOURCE

| | |
|-----------------------------|--------------------------|
| Philips CDM-SA/T 150W | 85 Lm/W, 6000 hr, 4000 K |
| GE Arcstream 150 W | 77 Lm/W, 6000 hr, 4000 K |

THERMAL

| | |
|---|----------------|
| Maximum ambient temperature (T_a) | 40° C (104° F) |
| Maximum surface temperature..... | 65° C (149° F) |

CONTROL AND PROGRAMMING

| | |
|-----------------------|----------------------|
| Control protocol..... | USITT DMX-512 (1990) |
| DMX channels..... | 1/6/7 |

CONNECTIONS

| | |
|----------------|--|
| AC input | 3-prong IEC male socket |
| Data | 3-pin locking XLR, pin 1 shield, pin 2 cold (-), pin 3 hot (+) |

MAXIMUM POWER AND CURRENT

| | |
|---------------------------|--------------|
| @ 100 V, 50 or 60 Hz..... | 205 W, 2.6 A |
| @ 120 V, 50 or 60 Hz..... | 205 W, 2.0 A |
| @ 210 V, 50 or 60 Hz..... | 190 W, 1.2 A |
| @ 230 V, 50 or 60 Hz..... | 190 W, 1.0 A |
| @ 250 V, 50 or 60 Hz..... | 200 W, 1.0 A |

FUSES

| | |
|-----------------------------|-------------------------------|
| Primary fuse | T 3.15 A, high I^2t , 250 V |
| Secondary fuse (F101) | T 2.0 A, 250 V |

INSTALLATION

| | |
|--|---------------|
| Minimum distance to combustible materials..... | 0.1 m (4 in) |
| Minimum distance to illuminated surfaces..... | 0.3 m (12 in) |
| Minimum clearance around fan and air vents | 0.1 m (4 in) |

ACCESSORIES

| | |
|---------------------------|----------|
| MC-1 controller, EU..... | 90718000 |
| MC-1 controller, US | 90718100 |
| G-clamp | 91602003 |
| Half-coupler clamp..... | 91602005 |