

VARI***LITE**

VL4000 BEAMWASH



The Vari-Lite VL4000 BeamWash is designed to provide designers, rental companies, venues and productions with a complement of fixtures offering unlimited design possibilities.

Without the need to change lenses, the VL4000 BeamWash combines stunning wash capabilities with intense beam functionality and the ability to produce a powerful collimated shaft of light. Producing 43,000 lumens in standard mode (35,000 studio mode), the VL4000 BeamWash uses a 1200W lamp to provide incredible point-of-source imagery through its 254mm (10") front lens.

When used in wash mode, the luminaire provides a 10 to 60 degree zoom range. By simply adjusting a DMX value, the VL4000 BeamWash can shift to an intense beam luminaire with an amazing 4 to 40 degree beam angle, or a Shaft fixture for a powerful, collimated ray of light where the 4 degree beam angle can be further reduced to near zero.



VL4000 BEAMWASH

FEATURES & BENEFITS

- 1200W Philips MSR Gold FastFit lamp
- Swap from wash to beam with no lens change
- Image projection is sharper than standard beam fixtures
- Studio mode for quitter application uses
- Multiple hanging rail points
- Dual opposing color wheels
- Infinity CMY cross fading system
- 2 fixed color wheels; five positions each
- Variable CTO color temperature correction
- Two gobo wheels; seven rotatable, indexable positions plus open
- Dual coated glass dimmer flags
- Dual blade strobe system
- Beam size iris
- 43,000 lumens (standard mode), 35,000 lumens (studio mode)
- One animation wheel; rotating indexable pattern with variable motion control
- Wash mode zoom range from 10-60° (6:1 optics system)
- Beam mode zoom range from 4-40° (10:1 optics system)
- Shaft mode zoom range from 4° to near 0°
- 5 facet step prism
- Beam and shaft mode indexing and rotating lenticular effect
- Wash mode indexing and rotating beam shaping
- Two year limited warranty

VL4000 BEAMWASH

SOURCE

Type	MSR
Lamp cap	PGJX50
Wattage	1200W

OPTICAL PERFORMANCE

Lumen output (max.)	Standard mode	43,000
	Studio mode	35,000
Color temperature	6000K	
CRI / Ra	>75	
Dimming system	Mechanical glass blades / independent dual strobe blades	

BEAM

Beam angle	Wash mode	10-60°
	Beam mode	4-40°
	Shaft mode	4°

COLOR

Color system	CMY, variable CTO 2 color wheel 5 + open
---------------------	--

IMAGING

Gobo 1	Gobo wheel 6 + open rotating
Gobo 2	Gobo wheel 6 + open rotating
Animation wheel	1 x Index / rotating animation wheel
Prism	5 facet linear
Frost	N/A
Framing shutters / beam shaping	Lenticular lens
Iris	Yes

MOVEMENT

Pan / tilt	540° / 270°
-------------------	-------------

COOLING


Fan	Yes
Studio mode	Yes

DATA PROTOCOLS

Controls	DMX512-A / RDM
DMX channels	46 / 41

VL4000 BEAMWASH

POWER			
Range		200-264VAC, 50/60Hz	
ENVIRONMENT		°C	°F
Operating temperature	Standard mode	-29-40°	-20-104°
	Studio mode	-29-50°	-20-122°
PHYSICALS			
IP rating		IP20	
Finish		Black	
Construction		Metal frame, engineering plastic covers	
DIMENSIONS		mm	in
H x W x L		890 x 735 x 567	35 x 29 x 22.3
Hanging centers		762	30
WEIGHT		kg	lb
Weight		45.8	101
WARRANTY & APPROBATION			
Warranty		2 years	
Approvals / listings		CE, ETL, UL, FCC CSA, RoHS, ISO 9001	




Note:
Shown with optional safety cables, clamps, etc.


VL4000 BEAMWASH

VL4000 BEAMWASH	ORDER CODE
Vari-Lite VL4000 BeamWash	20.9704.0002
Luminaire programing kit	PEGASUS

GOBOS



ANIMATION WHEEL



© 2018 Signify Holding. All rights reserved.

All trademarks are owned by Signify Holding or their respective owners. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Data subject to change.

Ref: 20.9704.0002-SpecSheet-01