

SPECIFICATIONS

B

PHYSICAL

Size (L x W x H): 296 x 269 x 270 mm (11.7 x 10.6 x 10.6 in)
Weight: 8.5 kg (18.7 lbs)

THERMAL

Maximum ambient temperature (Ta): 40° C (104° F)
Maximum surface temperature: 65° C (149° F)

CONTROL AND PROGRAMMING

DMX-512 (1990) control: 1 and 6 channel control modes
Stand-alone control: automatic & music trigger, master/slave configurable
Data pinout: 3-pin XLR - pin 1 shield, pin 2 cold (-), pin 3 hot (+)

AC SUPPLY

AC input: 3-pin IEC male socket
Wiring options: 100/120/210/230/250 V, 50/60 Hz

MAXIMUM POWER AND CURRENT

@ 100 V, 50 Hz 210 W, 2.9 A
@ 120 V, 60 Hz 205 W, 2.1 A
@ 210 V, 60 Hz 160 W, 1.1 A
@ 230 V, 50 Hz 205 W, 1.1 A
@ 250 V, 50 Hz 200 W, 1.1 A

FUSES

Primary fuse: T 3.15 A, high I²t, 250 V
Secondary fuse: T 2.0 A, 250 V

CONSTRUCTION

Housing: UV-resistant fiber-reinforced composite
Finish, black: integral color
Finish, titanium: polyurethane coating

INSTALLATION

Minimum distance to combustible materials: 0.1 m (4 in)
Minimum distance to illuminated surfaces: 0.3 m (12 in)
Minimum clearance around fan and air vents: 0.1 m (4 in)