

**ELATION® CUEPIX STRIP TRI™**  
**DMX Channel Values / Functions (19 DMX Channels)**

Specifications are subject to change without any prior written notice.

*\*Control of COB Modules depends on the Flip setting.*

MODE / CHANNEL					VALUE	FUNCTION
3 CH	6 CH	7 CH	15 CH	19 CH		
1	1	1				RED
					0-255	0 to 100%
2	2	2				GREEN
					0-255	0 to 100%
3	3	3				BLUE
					0-255	0 to 100%
	4					MASTER DIMMER
					0-255	Intensity 0 to 100%
			1	1		*RED - COB MODULE 1
					0-255	0 to 100%
			2	2		*GREEN - COB MODULE 1
					0-255	0 to 100%
			3	3		*BLUE - COB MODULE 1
					0-255	0 to 100%
			4	4		*RED - COB MODULE 2
					0-255	0 to 100%
			5	5		*GREEN - COB MODULE 2
					0-255	0 to 100%
			6	6		*BLUE - COB MODULE 2
					0-255	0 to 100%
			7	7		*RED - COB MODULE 3
					0-255	0 to 100%
			8	8		*GREEN - COB MODULE 3
					0-255	0 to 100%
			9	9		*BLUE - COB MODULE 3
					0-255	0 to 100%
			10	10		*RED - COB MODULE 4
					0-255	0 to 100%
			11	11		*GREEN - COB MODULE 4
					0-255	0 to 100%
			12	12		*BLUE - COB MODULE 4
					0-255	0 to 100%
			13	13		*RED - COB MODULE 5
					0-255	0 to 100%
			14	14		*GREEN - COB MODULE 5
					0-255	0 to 100%
			15	15		*BLUE - COB MODULE 5
					0-255	0 to 100%

traits  
**ELATION** | **CUEPIX STRIP TRI™** | dmx

ELATION® CUEPIX STRIP TRI™						
DMX Channel Values / Functions (19 DMX Channels)						
Specifications are subject to change without any prior written notice.						
*Control of COB Modules depends on the Flip setting.						
MODE / CHANNEL					VALUE	FUNCTION
3 CH	6 CH	7 CH	15 CH	19 CH		
						MACROS
					0-15	NO FUNCTION
					16-23	RED
					24-31	GREEN
					32-39	BLUE
					40-47	RED-GREEN
					48-55	GREEN-BLUE
					56-63	RED-BLUE
					64-71	RED-GREEN-BLUE
					72-79	Color Macro 1
					80-87	Color Macro 2
					88-95	Color Macro 3
					96-103	Color Macro 4
					104-111	Color Macro 5
					112-119	Color Macro 6
		4		16	120-127	Color Macro 7
					128-135	Color Macro 8
					136-143	DREAM Macro
					144-151	METEOR Macro
					152-159	FADE Macro
					160-167	CHANGE Macro
					168-175	FLOW Macro 1
					176-183	FLOW Macro 2
					184-191	FLOW Macro 3
					192-199	FLOW Macro 4
					200-207	FLOW Macro 5
					208-215	FLOW Macro 6
					216-223	FLOW Macro 7
					224-231	FLOW Macro 8
					232-239	FLOW Macro 9
					240-255	NO FUNCTION
						DIMMER / SPEED*
		5		17		**DIMMER Control ONLY when MACRO Channel DMX Value is (0-135) **SPEED Control ONLY when MACRO Channel DMX Value is (136-239)
					0-255	**DIMMER / SPEED Control SLOW to FAST
						FLASH / STROBE
	5	6		18	0-255	Flash / Strobe Effect SLOW to FAST
						DIMMING CURVE MODES
					0-41	STANDARD
					42-84	STAGE
	6	7		19	85-127	TV
					128-170	ARCHITECTURAL
					171-213	THEATRE
					214-255	Default to Unit Setting

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040

323-582-3322 | 323-832-9142 fax | [www.elationlighting.com](http://www.elationlighting.com) | [info@elationlighting.com](mailto:info@elationlighting.com)

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands

+31 45 546 85 66 | +31 45 546 85 96 fax | [www.elationlighting.eu](http://www.elationlighting.eu) | [info@elationlighting.eu](mailto:info@elationlighting.eu)