

Available in white or black

Opti RGB Dimensions

The Opti RGB by Elation Professional is a high output LED color changer featuring full RGB color mixing utilizing 24 LEDs - 8 red, 8 green, 8 blue running at 1W power each. The unit boasts a sturdy, high impact aluminum construction available in black or white casing. The Opti RGB is fan cooled with the design of the fixture optimized to provide up to 50,000 hours estimated LED life. This unit is rated at IP 20, designed for indoor applications and is available in both 120v or 240v models. This unit can be operated in stand alone mode, sound active mode or controlled via DMX controller. Control data input is via 3 pin XLR Neutrik™ serial first in and out connector cables. Heavy duty rigging yoke is included and optional safety cables and data cables are available. The Opti RGB comes fitted with a standard 25° lens kit. Optional 45° lens kit, barn doors, diffusion filter and mounting clamp are available options.

FEATURES

- High output L.E.D. Color Changer
- Powerful 24 x 1 Watt L.E.D.s (8 red, 8 green & 8 blue)
- Color strobe
- 15° beam angle
- Optional 45° beam angle lens kit available (part no. OptiRGB 45D Kit)
- Sturdy, high-impact aluminum construction
- Fan cooled
- Very low power consumption
- Very low heat output
- On-board DMX (addressable via 10 dip switches)
- Built-in sound active programs
- Optional barn doors (part no. OPTI/BDB)

TECHNICAL SPECIFICATIONS

- **DMX Channels:** 7 DMX Channels
- **Control:** USITT DMX-512, 3 pin XLR serial input/output
- **Dimmer:** 0 - 100% electronic dimming
- **Strobe:** Color strobe, 1-18 flashes per second
- **IP Rating:** IP 20
- **Power Supply:** 120V / 240V 50/60Hz
- **Power consumption:** 45W
- **Ballast:** Magnetic
- **Lamp:** 24 x 1W long-life L.E.D.s (8 red, 8 green & 8 blue)
- **Lamp Life:** 50,000 hrs. life
- **Dimensions:** (LxWxH-not including hanging bracket) 11.5" x 8.5" x 8.5" / 292mm x 215mm x 215mm
- **Weight:** 11 lbs / 5 kg
- **Rigging:** Heavy duty single rigging yoke



Opti RGB / Opti RGB WH



COLORS

- Total of 24 L.E.D.s (8 red, 8 green, 8 blue)
- Full RGB color mixing
- Manual control of colors for static color option



Optional 45° beam angle lens kit available (part no. OptiRGB 45D Kit)


PHOTOMETRICS

Opti RGB Photometric Beam Angle Data

Standard Beam Angle 15°

LUX x 0.0929 = FC


| | | | | | |
|----------|-------------------|-------------------|-------------------|-------------------|-------------------|
| R (8) | 111 FC / 1194 LUX | 3.7 FC / 39.8 LUX | 1.6 FC / 17.5 LUX | 0.9 FC / 10.1 LUX | 0.8 FC / 8.6 LUX |
| G (8) | 126 FC / 1358 LUX | 3.9 FC / 42.5 LUX | 2.4 FC / 25.7 LUX | 1.4 FC / 14.6 LUX | 0.9 FC / 9.5 LUX |
| B (8) | 13 FC / 136.4 LUX | 0.3 FC / 3.7 LUX | 0.2 FC / 2.5 LUX | 0.2 FC / 1.7 LUX | 0.1 FC / 1.2 LUX |
| RGB (24) | 217 FC / 2340 LUX | 18 FC / 192 LUX | 4.7 FC / 50.2 LUX | 1.8 FC / 19.7 LUX | 1.5 FC / 15.8 LUX |



Optional Beam Angle 45° (not included)

LUX x 0.0929 = FC

| | | | | | |
|----------|-------------------|-------------------|------------------|------------------|------------------|
| R (8) | 15.5 FC / 124 LUX | 0.5 FC / 5.6 LUX | 0.3 FC / 2.9 LUX | 0.2 FC / 1.9 LUX | 0.1 FC / 1.6 LUX |
| G (8) | 18.2 FC / 196 LUX | 0.6 FC / 6.4 LUX | 0.4 FC / 3.8 LUX | 0.2 FC / 2.3 LUX | 0.2 FC / 1.9 LUX |
| B (8) | 1.4 FC / 14.6 LUX | 0.1 FC / 1.6 LUX | 0.1 FC / 1.3 LUX | 0.09 FC / 1 LUX | 0.1 FC / 0.7 LUX |
| RGB (24) | 33.1 FC / 356 LUX | 1.7 FC / 18.1 LUX | 0.5 FC / 5.4 LUX | 0.3 FC / 2.9 LUX | 0.2 FC / 2.4 LUX |



DMX TRAITS

| Channel | Value | Function |
|---------|-----------|------------------------|
| 1 | 0 - 255 | Red (0% → 100%) |
| 2 | 0 - 255 | Green (0% → 100%) |
| 3 | 0 - 255 | Blue (0% → 100%) |
| 4 | 16 - 255 | Color macra |
| 5 | 0 - 15 | No function |
| | 16 - 255 | Strobe/speed control |
| 6 | 0 - 31 | No function |
| | | <i>Dimming Control</i> |
| | 32 - 63 | Dim → Bright |
| | 64 - 95 | Bright → Dim |
| | 96 - 127 | Dim → Bright → Dim |
| | 128 - 159 | Color mixing |
| | 160 - 191 | 3 color change |
| | 192 - 223 | 7 color chchange |
| | 224 - 255 | Sound active |
| 7 | 0 - 255 | Dimming (0% → 100%) |

| Product Order Code | Description |
|------------------------|------------------|
| OPTI RGB | Black OPTI RGB |
| OPTI RGB WH | White OPTI RGB |
| Accessories Order Code | Description |
| PRO CLAMP | Mounting Clamp |
| DF 64 | Diffusion filter |
| OPTI RGB 45D KIT | 45° Lens Kit |
| OPTI/BDB | Barn door |