

TTA076_SVC NOTES: APPLICABLE TO VIEWS THIS PAGE ONLY REMOVE PROTECTIVE LINER FROM THE 4 ADHESIVE PADS TO BOND THE DIFFUSION GLASS TO MOUNT PLATE. CENTER OVER APERTURE. FOR SERVICE 2. ENERGIZED MOTORS ARE REQUIRED TO PRODUCTION HOME FLAG ASSEMBLIES AGAINST THE CLOSED STOP. REFERENCE ONLY 3. ALIGN TOP EDGE OF FLAG ASSEMBLY TO BOTTOM GROOVE EDGE OF STOP FOR EACH FLAG CYAN #1 0 0 2 3 0 0 Ô \oplus 0 YELLOW +1-0 \blacksquare \bigcirc YELLOW •2 (<u>@</u>) 000 0 0 2 3 CYAN +2 UNLESS OTHERWISE SPECIFIED RELEASE DATE:

DIMENSIONAL TOLERANCES:
0 PLACE DECIMAL: ±0.25
1 PLACE DECIMAL: ±0.25
2 PLACE DECIMALS: ±0.15
ANGLES: ±0.15
ANGLES: ±0.5 High End 2105 GRACY FARMS LANE AUSTIN, TEXAS, 18158 (512) 836-2242 RESEARCH. INTERPRET DIMENSIONS PER ASME YI.4.5M-1994

ASME YI.4.5M-1994

DIMENSIONS ARE IN MILLIMETERS A1 DO NOT SCALE | SCALE: 0,750 PROPRIETARY NOTICE:

A THE SCHOOL OF THE WAY OF THE STATE OF THE STATE OF THE STATE OF THE SCHOOL OF THE STATE OF THE STATE OF THE SCHOOL DRAWING NO. TTA076_SVC